

## Rótula SI SI40-T-K-DURBAL - SI40-T-K-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/si40-t-k-durbal>


### SI40-T-K



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / bronze-PTFE composite

**Inner ring:**  
bearing steel, hardened, ground and  
spherical surface chromium plated

**Outer ring:**  
brass body pressed around, outer race  
lined with bronze-PTFE composite

**Lubrication:**  
maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
SI 40 TIK		40	M 42 x 2	49	33,00	91	53,0	65

type	measurement [mm]			d <sub>1</sub>	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	W	h			
SI / SIL 40 TIK	60	55	142	17		2,400

## CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952489841
Diâmetro interior	40 mm
Diâmetro exterior	91 mm
Espessura	49 mm
Tipo	-
Peso	2400 g
Linha	-
Lubrificação	-
Embalagem	-

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE