

Rótula SA DSAL6-T-K-DURBAL - DSAL6-T-K-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/sa/dsal6-t-k-durbal>

DSAL6-T-K



male thread; maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C ₁	d ₂	
DSAL 6 T/K		6	M 6	9	6,75	20	

type	measurement [mm]		h	α [°]	Tragzahlen C ₁₀ [kN]	weight [kg]
	l ₁ min	l ₂				
DSA / DSAL 6 T/K	21		36	13	7,7	0,020

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952489940
Diâmetro interior	6 mm
Diâmetro exterior	20 mm
Espessura	9 mm
Tipo	SA
Peso	20 g
Linha	Rosca esquerda
Lubrificação	sem
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE