

Rótula SA

SSA12-T-K-DURBAL - SSA12-T-K-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/sa/ssa12-t-k-durbal>

SSA12-T-K



male thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

rod end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]				
SSA 12 T/K	12	M 12	16	12,00	32		

type	measurement [mm]		h	alpha [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂ min				
SSA / SSAL 12 T/K	32	54	13	24,0	0,085	

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952490700
Diâmetro interior	12 mm
Diâmetro exterior	32 mm
Espessura	16 mm
Tipo	SA
Peso	85 g
Linha	Rosca direita
Lubrificação	sem
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE