

Rótula SA

SSA16-T-K-DURBAL - SSA16-T-K-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/sa/ssa16-t-k-durbal>

SSA16-T-K



male thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

rod end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	d	G	B	C1	d2
SSA 16 T/K	16	M 16	21	15,00	42

type	measurement [mm]			alpha [°]	load rating C0 [kN]	weight [kg]
	l1 min	l2 min	h			
SSA / SSAL 16 T/K	37	21	66	15	39,0	0,210

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952490786
Diâmetro interior	16 mm
Diâmetro exterior	42 mm
Espessura	21 mm
Tipo	SA
Peso	210 g
Linha	Rosca direita
Lubrificação	sem
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE