

Rótula SI

DSSI5-T-K-DURBAL - DSSI5-T-K-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/dssi5-t-k-durbal>

DSSI5-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]						
DSSI 5 T/K	5	M 5	8	B	C1	d1	d2	d3	d4
				8	6,00	18	8,5	11	

type	measurement [mm]				load rating C ₀ [kN]	weight [kg]
	l _s min	W	h	α		
DSSI / DSSIL 5 T/K	10	9	27	13	6,0	0,016

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952491059
Diâmetro interior	5 mm
Diâmetro exterior	18 mm
Espessura	8 mm
Tipo	SI
Peso	16 g
Linha	Rosca direita
Lubrificação	sem
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE