

Rótula SI DSSIL10-T-K-DURBAL - DSSIL10-T-K-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/dssil10-t-k-durbal>

DSSIL10-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
DSSIL 10 T/K			d	G	B	C1	d1	d2	d3	d4
			10	M 10	14	10,50	28	15,0	19	

type	l1 min	W	h	α	load rating C0 [kN]	weight [kg]
DSSIL / DSSIL 10 T/K	20	17	43	13	18,0	0,077

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952491172
Diâmetro interior	10 mm
Diâmetro exterior	28 mm
Espessura	14 mm
Tipo	SI
Peso	77 g
Linha	Rosca esquerda
Lubrificação	sem
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE