

## Rótula SI DSSIL12-T-K-DURBAL - DSSIL12-T-K-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/dssil12-t-k-durbal>

### DSSIL12-T-K



female thread; maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
DSSIL 12 T/K			d	G	B	C <sub>1</sub>	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
			12	M 12	16	12,00	32	17,5	22	

type	measurement [mm]			load rating	weight
	l <sub>1</sub> min	W	h	C <sub>0</sub> (kg)	kg
DSSi / DSSIL 12 T/K	22	19	50	24,0	0,100

## CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952491264
Diâmetro interior	12 mm
Diâmetro exterior	32 mm
Espessura	16 mm
Tipo	SI
Peso	100 g
Linha	Rosca esquerda
Lubrificação	sem
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE