

## Rótula SI

### SSI25-T-K-DURBAL - DSSI25-T-K-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/dssi25-t-k-durbal>

#### SSI25-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	d	G	B	C1	d1	d2	d3	d4
right hand thread SSI 25 T/K	25	M 24 x 2	31	22,00	60	33,5	42	

type	l1 min	W	h	α	load rating C0 (kN)	weight Bgl
SSI / SSI 25 T/K	42	36	94	15	85,0	0,720

## CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952491615
Diâmetro interior	25 mm
Diâmetro exterior	60 mm
Espessura	31 mm
Tipo	SI
Peso	720 g
Linha	Rosca direita
Lubrificação	sem
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE