

Rótula SI

SSI30-T-K-DURBAL - SSI30-T-K-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/ssi30-t-k-durbal>

SSI30-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
			d	G	B	C1	d1	d2	d3	d4
SSI 30 T/K			30	M 30 x 2	37	25,00	70	40,0	50	

type	l1 min	W	h	α	load rating C0 [kN]	weight [kg]
SSI / SSI 30 T/K	51	41	110	17	114,0	1,100

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952491691
Diâmetro interior	30 mm
Diâmetro exterior	70 mm
Espessura	37 mm
Tipo	SI
Peso	1100 g
Linha	Rosca direita
Lubrificação	sem
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE