

Rótula SA

GAR20-UK-DURBAL - GAR20-UK-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/sa/gar20-uk-durbal>

GAR20-UK



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number	d	G	B	C ₁	d ₂
GAR 20 UK	20	M 20 x 1,5	16	13,0	53

type	l, min	measurement [mm] l ₁ min	h	α [°]	load rating C ₀ [kN]	weight [kg]
GAR / GAL 20 UK	43	27	78	9	60,0	0,310

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952493053
Diâmetro interior	20 mm
Diâmetro exterior	53 mm
Espessura	16 mm
Tipo	SA
Peso	310 g
Linha	Rosca direita
Lubrificação	sem
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE