

# Rótula GE

## GAR35-UK-2RS-DURBAL - DGAR35-UK-2RS-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/ge/dgar35-uk-2rs-durbal>

### GAR35-UK-2RS



male thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.


Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
steel body ground around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free



order number	measurement (mm)	
GAR 35 UK-2RS	d	G
	35	M 36 x 3
	s	C <sub>1</sub>
	25	21,0
		d <sub>2</sub>
		82

type	l, min	measurement (mm)	h	α [°]	load rating	weight
GAR / GAL 35 UK-2RS	82	42	140	6	146,0	1,400

## CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3616060467621
Diâmetro interior	35 mm
Diâmetro exterior	82 mm
Espessura	25 mm
Tipo	GE
Peso	1400 g
Linha	Rosca direita
Lubrificação	sem
Embalagem	1
Padrão	Nenhuma norma

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE