

Rótula SI

DGIR6-UK-DURBAL - GIR6-UK-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/gir6-uk-durbal>

DGIR6-UK



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE fabric

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free

order number	right hand thread	left hand thread	measurement [mm]					
			d	G	B	C ₁	d ₂	d ₄
DGIR 6 UK			6	M 6	6	4,4	21	10,0 13

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	t ₃ min	h	W			
DGIR / DGIL 6 UK	11	30	11	13	8,2	0,021

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952493565
Diâmetro interior	6 mm
Diâmetro exterior	21 mm
Espessura	6 mm
Tipo	SI
Peso	21 g
Linha	Rosca direita
Lubrificação	sem
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE