


Rótula SI
GIL6-UK-DURBAL - GIL6-UK-DURBAL
<https://www.123rolamento.pt/rolamento-mancal/rotula/si/gil6-uk-durbal>

GIL6-UK

female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq 35$ with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter $d \geq 17$ additional seal on both sides upon request.



FERROBAL

Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
no lubrication necessary, maintenance free

order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₄
GIL 6 UK		6	M 6	6	4,4	21	10,0 13

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	l ₃ min	h	W			
GIR / GIL 6 UK	11	30	11	13	8,2	0,021

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952493589
Diâmetro interior	6 mm
Diâmetro exterior	21 mm
Espessura	6 mm
Tipo	SI
Peso	21 g
Linha	Rosca esquerda
Lubrificação	sem
Embalagem	1

contato@123rolamento.pt
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE