

Rótula SI GIL8-UK-DURBAL - GIL8-UK-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/gil8-uk-durbal>

GIL8-UK



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE fabric

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free

order number	d	G	B	measurement [mm]	C ₁	d ₂	d ₄
GIL 8 UK	8	M 8	8	6,0	24	12,5	16

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	t ₃ min	h	W			
GIR / GIL 8 UK	15	36	14	15	12,9	0,039

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952493619
Diâmetro interior	8 mm
Diâmetro interior	0.315" inch
Diâmetro exterior	24 mm
Diâmetro exterior	0.945" inch
Espessura	8 mm
Espessura	0.315" inch
Tipo	SI
Peso	39 g
Linha	Rosca esquerda
Lubrificação	sem
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE