

Rótula SI

GIR12-UK-DURBAL - GIR12-UK-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/gir12-uk-durbal>

GIR12-UK



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE fabric

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free

order number	d	G	B	measurement [mm]	C ₁	C ₂	d ₂	d ₄
GIR 12 UK	12	M 12	10	8,0	34	17,5	22	

type	measurement [mm]				α [°]	load rating C ₀ [kN]	weight [kg]
	t ₃ min	h	W				
GIR / GRL 12 UK	23	50	19		11	24,5	0,096

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952493695
Diâmetro interior	12 mm
Diâmetro exterior	34 mm
Espessura	10 mm
Tipo	SI
Peso	96 g
Linha	Rosca direita
Lubrificação	sem
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE