

Rótula SI

GIR17-UK-DURBAL - GIR17-UK-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/gir17-uk-durbal>

GIR17-UK



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE fabric

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free

order number	d	G	B	C ₁	d ₂	d ₄
GIR 17 UK	17	M 16	14	11,0	46	24,0

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	l ₃ min	h	W			
GIR / GIR 17 UK	34	67	27	10	45,0	0,220

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952493817
Diâmetro interior	17 mm
Diâmetro exterior	46 mm
Espessura	14 mm
Tipo	SI
Peso	220 g
Linha	Rosca direita
Lubrificação	sem
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE