

Rótula SI GIR25-UK-DURBAL - GIR25-UK-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/gir25-uk-durbal>

GIR25-UK



female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number	d	G	B	C ₁	d ₂	d ₄
GIR 25 UK	25	M 24 x 2	20	17,0	64	33,5

type	measurement [mm]				load rating C ₀ [kN]	weight [kg]
	l ₃ min	h	W	α [°]		
GIR / GIR 25 UK	48	94	36	7	83,0	0,640

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952493978
Diâmetro interior	25 mm
Diâmetro exterior	64 mm
Espessura	20 mm
Tipo	SI
Peso	640 g
Linha	Rosca direita
Lubrificação	sem
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE