

## Rótula SI GIR30-UK-2RS-DURBAL - GIR30-UK-2RS-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/gir30-uk-2rs-durbal>

### GIR30-UK-2RS



**female thread:** maintenance free, according to DIN ISO 12240-4; series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.

**Rod end body:** surface zinc plated

**Sliding combination:** steel / bronze-PTFE fabric

**Inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:** steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** no lubrication necessary, maintenance free

order number	measurement [mm]					
GIR 30 UK (-2RS)	d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>4</sub>
	30	M 30 x 2	22	19,0	73	40,0 50

type	measurement [mm]			$\alpha$ [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	t <sub>3</sub> min	h	W			
GIR / GIL 30 UK	56	110	41	6	110,0	0,930

## CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
N° Ean13	3663952494012
Diâmetro interior	30 mm
Diâmetro exterior	73 mm
Espessura	22 mm
Tipo	SI
Peso	930 g
Linha	Rosca direita
Lubrificação	sem
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE