

Rótula SI

GIR35-UK-2RS-DURBAL - GIR35-UK-2RS-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/gir35-uk-2rs-durbal>

GIR35-UK-2RS



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE fabric

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free

order number	right hand thread	left hand thread	measurement [mm]						
			d	G	B	C ₁	d ₂	d ₄	
GIR 35 UK-2RS			35	M 36 x 3	25	21,0	82	47,0	58

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	t ₃ min	h	W			
GIR / GIL 35 UK-2RS	60	125	50	6	146,0	1,300

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952494081
Diâmetro interior	35 mm
Diâmetro exterior	82 mm
Espessura	25 mm
Tipo	SI
Peso	1300 g
Linha	Rosca direita
Lubrificação	sem
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE