

## Rótula SI GIR45-UK-2RS-DURBAL - GIR45-UK-2RS-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/gir45-uk-2rs-durbal>

### GIR45-UK-2RS



**female thread: maintenance free, according to DIN ISO 12240-4; series E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.

**Rod end body:** surface zinc plated

**Sliding combination:** steel / bronze-PTFE fabric

**Inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:** steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** no lubrication necessary, maintenance free

order number	right hand thread	left hand thread	measurement [mm]						
			d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>4</sub>	
GIR 45 UK-2RS			45	M 42 x 3	32	27,0	102	58,0	70

type	measurement [mm]			$\alpha$ [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	t <sub>3</sub> min	h	W			
GIR / GIL 45 UK-2RS	65	145	60	7	240,0	2,500

## CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
N° Ean13	3663952494166
Diâmetro interior	45 mm
Diâmetro interior	1.772" inch
Diâmetro exterior	102 mm
Diâmetro exterior	4.016" inch
Espessura	32 mm
Espessura	1.26" inch
Tipo	SI
Peso	2500 g
Linha	Rosca direita
Lubrificação	sem
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE