

Rótula SI GIR50-UK-2RS-DURBAL - GIR50-UK-2RS-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/gir50-uk-2rs-durbal>

GIR50-UK-2RS



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE fabric

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free

order number	measurement [mm]						
GIR 50 UK-2RS	d	G	B	C ₁	C ₂	d ₂	d ₄
	50	M 45 x 3	35	30,0	112	62,0	75

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	l ₃ min	h	W			
GIR / GIR 50 UK-2RS	68	160	65	6	290,0	3,500

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952494210
Diâmetro interior	50 mm
Diâmetro exterior	112 mm
Espessura	35 mm
Tipo	SI
Peso	3500 g
Linha	Rosca direita
Lubrificação	sem
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE