

## Rótula SI

### GIR80-UK-2RS-DURBAL - GIR80-UK-2RS-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/gir80-uk-2rs-durbal>

#### GIR80-UK-2RS



**female thread:** maintenance free, according to DIN ISO 12240-4; series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.

**Rod end body:** surface zinc plated

**Sliding combination:** steel / bronze-PTFE fabric

**Inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:** steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** no lubrication necessary, maintenance free

order number	right hand thread	left hand thread	measurement [mm]					
	d	G	B	C <sub>1</sub>	C <sub>2</sub>	d <sub>2</sub>	d <sub>4</sub>	
GIR 80 UK-2RS	80	M 64 x 4	55	47,0	180	95,0	110	

type	measurement [mm]			α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	t <sub>3</sub> min	h	W			
GIR / GIL 80 UK-2RS	85	230	100	6	750,0	12,000

## CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
N° Ean13	3663952494326
Diâmetro interior	80 mm
Diâmetro exterior	180 mm
Espessura	55 mm
Tipo	SI
Peso	12000 g
Linha	Rosca direita
Lubrificação	sem
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE