

Rótula SA DSAZPL25-S-DURBAL - DSAZPL25-S-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/sa/dsazpl25-s-durbal>


DSAZPL25-S



male thread:
lubrication
required,
similar to
DIN ISO 12240-4:
series R,
measurement in
inches



Description: DIN ISO rod end K series. Dimensions in
inch. Sliding combination steel / heavy duty bronze.
With grease nipple.



Rod end body:
surface zinc plated

Sliding combination:
steel / heavy duty bronze

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
heavy duty bronze with lubrication

Lubrication:
lubrication required, with grease nipple

order number	right hand thread	left hand thread	measurement [mm]				
			d	G	B	C ₁	d ₂
DSAZPL 25 S			25,40	5/16 - 12	34,93	25,40	69,85

type	inches	measurement [mm]		α [°]	load rating C ₀ [kN]	weight [kg]
		l ₁ min	h			
DSAZP / DSAZPL 25 S	1"	53,98	104,78	14	101,0	1,100

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952496320
Diâmetro interior	25.4 mm
Diâmetro interior	1" inch
Diâmetro exterior	69.85 mm
Diâmetro exterior	2 3/4" inch
Espessura	34.93 mm
Espessura	1 3/8" inch
Tipo	SA
Peso	1100 g
Linha	Rosca esquerda
Lubrificação	sem
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE