

## Rótula SI SIZJL12-DURBAL - SIZJL12-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/sizjl12-durbal>

### SIZJL12



**female thread:**  
lubrication  
required,  
similar to  
DIN ISO 12240-4,  
series K,  
measurement in  
inches

**Description:** DIN ISO rod end K series. Dimensions  
in inch. Sliding combination steel / steel.  
Size ≥ 9 with grease nipple can be mounted upon  
request.

**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and  
spherical surface chromium plated

**Outer ring:**  
rod end body pressed around inner ring

**Lubrication:**  
lubrication required

order number	d	B	C <sub>1</sub>	d <sub>2</sub>	G	d <sub>3</sub>	d <sub>4</sub>
<b>SIZJL 12</b>	12,70	15,88	11,50	33,32	1/2 - 20	18,67	22,23

  

type	inches	l <sub>1</sub> min	measurement [mm]	h	α	load rating	weight
SIZJ / SIZJL 12	1 / 2 "	25,40	19,05	53,98	10,0	28,0 (KN)	0,132 (kg)

## CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952496863
Diâmetro interior	12.7 mm
Diâmetro exterior	33.32 mm
Espessura	15.88 mm
Tipo	SI
Peso	132 g
Linha	Rosca esquerda
Lubrificação	sem
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE