

Rótula SI SIL25-ES-DURBAL - SIL25-ES-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/sil25-es-durbal>

SIL25-ES



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number
right hand thread left hand thread

SIL 25 ES	d	G	measurement [mm]				
			B	C ₁	d ₂	d ₄	
SIL 25 ES	25	M 24 x 2	20	17,0	64	33,5	42

measurement [mm]

type	l ₃ min	measurement [mm]			load rating C ₀ [kN]	weight [g]
		W	h	α [°]		
SI / SIL 25 ES	48	36	94	7	83,0	0,64

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952497150
Diâmetro interior	25 mm
Diâmetro exterior	64 mm
Espessura	20 mm
Tipo	SI
Peso	640 g
Linha	Rosca esquerda
Lubrificação	com
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE