

Rótula SI SI30-ES-DURBAL - SI30-ES-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/si30-es-durbal>

SI30-ES



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number
right hand thread left hand thread

SI 30 ES	d	G	measurement (mm)				
			B	C ₁	d ₂	d ₄	
	30	M 30 x 2	22	19,0	73	40,0	50

measurement [mm]

type	l ₃ min	measurement [mm]			load rating C ₀ [kN]	weight [kg]
		W	h	α [°]		
SI / SII 30 ES	56	41	110	6	110,0	0,93

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952497235
Diâmetro interior	30 mm
Diâmetro exterior	73 mm
Espessura	22 mm
Tipo	SI
Peso	930 g
Linha	Rosca direita
Lubrificação	com
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE