

Rótula SI SI35-ES-2RS-DURBAL - SI35-ES-2RS-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/si35-es-2rs-durbal>

SI35-ES-2RS



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number
right hand thread left hand thread

SI 35 ES (-2RS)

type	measurement [mm]			α [°]	load rating C_0 [kN]	weight [kg]
	l_2 min	W	h			
SI / SII 35 ES (-2RS)	60	50	125	6	146,0	1,3

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952497358
Diâmetro interior	35 mm
Diâmetro interior	1.378" inch
Diâmetro exterior	82 mm
Diâmetro exterior	3.228" inch
Espessura	25 mm
Espessura	0.984" inch
Tipo	SI
Peso	1300 g
Linha	Rosca direita
Lubrificação	com
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE