

Rótula SI

SI40-ES-2RS-DURBAL - SI40-ES-2RS-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/si40-es-2rs-durbal>

SI40-ES-2RS



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number
right hand thread left hand thread

SI 40 ES (-2RS)	d	G	B	C ₁	d ₂	d ₃	d ₄
	40	M 39 x 3	28	23,0	92	52,0	65

measurement [mm]

type	l ₃ min	W	h	α [°]	load rating C ₀ [kN]	weight [kg]
SI / SII 40 ES (-2RS)	65	55	142	7	180,0	2,0

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952497389
Diâmetro interior	40 mm
Diâmetro exterior	92 mm
Espessura	28 mm
Tipo	SI
Peso	2000 g
Linha	Rosca direita
Lubrificação	com
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE