

## Rótula SI SIL40-ES-2RS-DURBAL - SIL40-ES-2RS-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/sil40-es-2rs-durbal>

### SIL40-ES-2RS



**female thread;**  
**lubrication**  
**required,**  
**according to**  
**DIN ISO 12240-4;**  
**series E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSI...ES-2RS with additional seals also available.

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and phosphated

**Outer ring:**  
bearing steel, hardened, ground and phosphated

**Lubrication:**  
lubrication required

**order number**

right hand thread	left hand thread	measurement (mm)						
d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	W	
SIL 40 ES (-2RS)		40	M 39 x 3	28	23,0	92	52,0	65

**type**

type	l <sub>3</sub> min	W	h	$\alpha$ [°]	load rating C <sub>0</sub> (kN)	weight (kg)
SI / SIL 40 ES (-2RS)	65	55	142	7	180,0	2,0

## CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952497433
Diâmetro interior	40 mm
Diâmetro exterior	92 mm
Espessura	28 mm
Tipo	SI
Peso	2000 g
Linha	Rosca esquerda
Lubrificação	com
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE