

Rótula SI

SIL45-ES-2RS-DURBAL - SIL45-ES-2RS-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/sil45-es-2rs-durbal>

SIL45-ES-2RS



female thread; lubrication required, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

Order number table:

order number	right hand thread	left hand thread	measurement (mm)						
SIL 45 ES (-2RS)			d	G	B	C ₁	d ₂	d ₃	d ₄
SIL 45 ES (-2RS)			45	M 42 x 3	32	27,0	102	58,0	70

Measurement table:

type	l ₃ min	W	h	α [°]	load rating C ₀ [kN]	weight [kg]
SI / SIL 45 ES (-2RS)	65	60	145	7	240,0	2,5

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952497464
Diâmetro interior	45 mm
Diâmetro interior	1.772" inch
Diâmetro exterior	102 mm
Diâmetro exterior	4.016" inch
Espessura	32 mm
Espessura	1.26" inch
Tipo	SI
Peso	2500 g
Linha	Rosca esquerda
Lubrificação	com
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE