

Rótula SI

SIL50-ES-2RS-DURBAL - SIL50-ES-2RS-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/sil50-es-2rs-durbal>

SIL50-ES-2RS



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

Rod end body:
surface zinc plated

order number		measurement [mm]	
right hand thread	left hand thread	d	G
SIL 50 ES (-2RS)		50	M 45 x 3

type	measurement [mm]			α [°]	load rating C_0 [kN]	weight [kg]
	l_1 min	W	h			
SI / SIL 50 ES (-2RS)	68	65	160	6	290,0	3,5

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952497594
Diâmetro interior	50 mm
Diâmetro exterior	112 mm
Espessura	35 mm
Tipo	SI
Peso	3500 g
Linha	Rosca esquerda
Lubrificação	com
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE