

Rótula SA SA12-E-DURBAL - SA12-E-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/sa/sa12-e-durbal>

SA12-E



male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.


Ball end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary



order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
SA 12 E		12	M 12	10	8,0	34

type	measurement [mm]				n [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂	h				
SA / SA 12 E	28	17	54	11	24,5	0,085	

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952497990
Diâmetro interior	12 mm
Diâmetro exterior	34 mm
Espessura	10 mm
Tipo	SA
Peso	86 g
Linha	Rosca direita
Lubrificação	com
Embalagem	-
Padrão	Nenhuma norma

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE