

Rótula SA SA25-ES-DURBAL - DSA25-ES-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/sa/dsa25-es-durbal>

SA25-ES



male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.


Ball end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary



order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
SA 25 ES		25	M 24 x 2	20	17,0	64

type	measurement [mm]			n [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂	h			
SA / SAL 25 ES	53	32	94	7	83,0	0,560

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952498317
Diâmetro interior	25 mm
Diâmetro interior	0.984" inch
Diâmetro exterior	64 mm
Diâmetro exterior	2.52" inch
Espessura	20 mm
Espessura	0.787" inch
Tipo	SA
Peso	560 g
Linha	Rosca direita
Lubrificação	com
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE