

Rótula SA

SAL30-ES-DURBAL - SAL30-ES-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/sa/sal30-es-durbal>

SAL30-ES



male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.

Bad end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary

order number	measurement [mm]
right hand thread	d
left hand thread	G
SAL 30 ES	30 M 30 x 2
	B
	C ₁
	d ₂

type	measurement [mm]	n	load rating	weight
SA / SAL 30 ES	l ₁ min 65 l ₂ 37 h 110	6	C ₀ (N) 110,0	(kg) 0,890

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952498386
Diâmetro interior	30 mm
Diâmetro exterior	73 mm
Espessura	22 mm
Tipo	SA
Peso	890 g
Linha	Rosca esquerda
Lubrificação	com
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE