

Rótula SA

SAL30-ES-2RS-DURBAL - SAL30-ES-2RS-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/sa/sal30-es-2rs-durbal>

SAL30-ES-2RS



male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.


Ball end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary



order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C ₁	d ₂	
	SAL 30 ES (-2RS)	30	M 30 x 2	22	19,0	73	

type	measurement [mm]				n [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂	h				
SA / SAL 30 ES (-2RS)	65	37	110	6	110,0	0,890	

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952498393
Diâmetro interior	30 mm
Diâmetro exterior	73 mm
Espessura	22 mm
Tipo	SA
Peso	890 g
Linha	Rosca esquerda
Lubrificação	com
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE