

## Rótula SA

### SAL40-ES-DURBAL - SAL40-ES-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/sa/sal40-es-durbal>

#### SAL40-ES



**male thread:**  
lubrication  
is necessary,  
according to  
DIN ISO 12240-4,  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSA...ES-2RS with additional seals also available.

**Ball end body:**  
surface zinc plated

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and phosphated

**Outer ring:**  
bearing steel, hardened, ground and phosphated

**Lubrication:**  
lubrication is necessary

order number	measurement [mm]
right hand thread	d G B C1 d2
left hand thread	
<b>SAL 40 ES</b>	40 M 39 x 3 28 23,0 92

type	measurement [mm]	n	load rating	weight
	l1 min l2 h	[°]	C0 [kN]	[kg]
SA / SAL 40 ES	86 46 150	7	180,0	1,800

## CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952498546
Diâmetro interior	40 mm
Diâmetro exterior	92 mm
Espessura	28 mm
Tipo	SA
Peso	1800 g
Linha	Rosca esquerda
Lubrificação	com
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE