

Rótula TAPR

GIHO-KL-20DO-DURBAL - GIHO-KL-20DO-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/tapr/giho-kl-20do-durbal>

GIHO-KL-20DO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE- ES pressed into rod end housing. Sliding combination steel/steel with grease nipple.

female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple

order number	measurement [mm]	
right hand thread	left hand thread	
GIHO-KL 20 DO*		
	20	24,1 55 M 14 x 1,5 25 55 16 13 17

type	measurement [mm]				α [°]	load rating C_0 [kN]	weight [kg]
	h_1	l_1	l_2	l_3			
GIHO-K / GIHO-KL 20 DO	58	19	85,5	25	9	42,5	0,43

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952500690
Diâmetro interior	20 mm
Diâmetro exterior	55 mm
Espessura	13 mm
Tipo	TAPR
Peso	430 g
Linha	Rosca esquerda
Lubrificação	com
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE