

## Rótula TAPR GIHO-K-30DO-DURBAL - GIHO-K-30DO-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/tapr/giho-k-30do-durbal>

### GIHO-K-30DO



**Description:** Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE- ES pressed into rod end housing. Sliding combination steel/steel with grease nipple.

**female thread:** hydraulic rod ends, according to DIN 24555

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication required

\* without grease nipple

order number	right hand thread	left hand thread	measurement [mm]								
GIHO-K 30 DO			d	d <sub>1</sub>	d <sub>2</sub>	G	d <sub>4</sub>	d <sub>5</sub>	B	C <sub>1</sub>	C <sub>2</sub>
			30	34,2	80	M 20 x 1,5	36	77	22	19	19

type	h <sub>1</sub>	l <sub>1</sub>	l <sub>2</sub>	α [°]	load rating C <sub>0</sub> [N]	weight [kg]
GIHO-K / GIHO-KL 30 DO	85	29	125,0	35	6	108,0

## CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952500768
Diâmetro interior	30 mm
Diâmetro exterior	80 mm
Espessura	19 mm
Tipo	TAPR
Peso	1250 g
Linha	Rosca direita
Lubrificação	com
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE