

Rótula TAPR GIHO-K-80DO-DURBAL - GIHO-K-80DO-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/tapr/giho-k-80do-durbal>

GIHO-K-80DO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE- ES pressed into rod end housing. Sliding combination steel/ steel with grease nipple.

female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple

order number	right hand thread	left hand thread	measurement [mm]								
GIHO-K 80 DO			d	d ₁	d ₂	G	d ₄	d ₅	B	C ₁	C ₂
			80	89,4	205	M 48 x 2	90	156	55	47	47

type	measurement [mm]				α [°]	load rating C ₀ [kN]	weight [kg]
GIHN-K / GIHN-KL 80 DO	h ₁	l ₁	l ₂	l ₃	6	585,0	15,00
	185	64	287,5	82			

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952500928
Diâmetro interior	80 mm
Diâmetro interior	3.15" inch
Diâmetro exterior	205 mm
Diâmetro exterior	8.071" inch
Espessura	47 mm
Espessura	1.85" inch
Tipo	TAPR
Peso	15000 g
Linha	Rosca direita
Lubrificação	com
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE