

## Rótula GEG GE12-LO-DURBAL - GE12-LO-DURBAL


<https://www.123rolamento.pt/rolamento-mancal/rotula/geg/ge12-lo-durbal>

### GE12-LO



**Description:** spherical plain bearing with sliding combination steel / steel. Inner ring with cylindrical extension at both sides. Lubrication groove and hole in inner and outer ring. Outer ring of type DGE...HO-2RS with two seals.

spherical plain bearing; similar to DIN ISO 12240-1, series W



**Sliding combination:**

steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated, with cylindrical extension on both sides

**Outer ring:** bearing steel, hardened, ground and phosphated, single split in axial direction

**Lubrication:** lubrication required

order number	d	B	C	d <sub>2</sub> min	D
GE 12 LO	12	12	7	15,5	22

type	measurement [mm]			r <sub>s</sub> [°]	load rating C <sub>10</sub> [N]	weight [kg]
	r <sub>15</sub> min	r <sub>25</sub> min	d <sub>1</sub>			
GE 12 LO	0,3	0,3	18,0	4	53	0,022

## CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952506364
Diâmetro interior	12 mm
Diâmetro exterior	22 mm
Espessura	7 mm
Tipo	GEG
Peso	22 g
Lubrificação	com
Embalagem	-
Padrão	Nenhuma norma

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE