

Rótula GEG GE50-LO-DURBAL - GE50-LO-DURBAL


<https://www.123rolamento.pt/rolamento-mancal/rotula/geg/ge50-lo-durbal>

GE50-LO



Description: spherical plain bearing with sliding combination steel / steel. Inner ring with cylindrical extension at both sides. Lubrication groove and hole in inner and outer ring. Outer ring of type DGE...HO-2RS with two seals.

spherical plain bearing; similar to DIN ISO 12240-1, series W



Sliding combination:

steel / steel

Inner ring: bearing steel, hardened, ground and phosphated, with cylindrical extension on both sides

Outer ring: bearing steel, hardened, ground and phosphated, single split in axial direction

Lubrication: lubrication required

order number	d	B	C	d ₂ min	D
GE 50 LO	50	50	28	57.0	75

type	measurement [mm]		d ₂	r ₁	load rating C ₁₀ [N]	weight [kg]
	r ₁ min	r ₂ min				
GE 50 LO	0.6	1.0	66.0	4	780	0.560

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
N° Ean13	3663952506500
Diâmetro interior	50 mm
Diâmetro interior	1.969" inch
Diâmetro exterior	75 mm
Diâmetro exterior	2.953" inch
Espessura	28 mm
Espessura	1.102" inch
Tipo	GEG
Peso	560 g
Lubrificação	com
Embalagem	-
Padrão	Nenhuma norma

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE