

Rótula SA

BRTM20-00-501-DURBAL - BRTM20-00-501-DURBAL

<https://www.123rolamento.pt/rolamento-manca/rotula/sa/brtm20-00-501-durbal>

BRTM20-00-501



male thread:
long-term
lubrication,
low maintenance,
shields,
adapter sizes
according to
DIN ISO 12240-4,
series K

**DURBAL® heavy-duty rod ends
with integral self-aligning
roller bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI

liner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminum-complex soap grease,
temperature range: -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]								
type	right hand thread	left hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	b ₁	b ₂	b ₃
BRTM 20 -00	-501		20	M 20 x 1,5	24,5	50	25	18		
measurements [mm]		weight	rotational speed limit	basic load rating						
type	h	l	b ₃	α	stat. C	dyn. C ₁₀				
BRTM 20	78	47	28	7,0	0,340	825	17000	11700		

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952506760
Diâmetro interior	20 mm
Diâmetro exterior	50 mm
Espessura	25 mm
Tipo	SA
Peso	340 g
Linha	Rosca direita
Lubrificação	com
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE