

Rótula SA

PM06-02-501-DURBAL - PM06-02-501-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/sa/pm06-02-501-durbal>

PM06-02-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]		measurements [mm]		weight		rotational speed limit		basic load rating	
type	type	d1	d2	d4	d5	Y	Yc	nmax [min ⁻¹]	C [N]	C0 [N]	stat. [N]
PM 06 -02 -501		6	M 10 x 1	8,5	24	1,28	1,34	1300	2445	765	

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952507491
Diâmetro interior	6 mm
Diâmetro interior	0.236" inch
Diâmetro exterior	24 mm
Diâmetro exterior	0.945" inch
Espessura	14 mm
Espessura	0.551" inch
Tipo	SA
Peso	57 g
Linha	Rosca direita
Lubrificação	com
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE