

Rótula SA

PM08-00-502-DURBAL - PM08-00-502-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/sa/pm08-00-502-durbal>

PM08-00-502



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]			weight			rotational speed limit			basic load rating			
type	type	d1	d2	d3	d4	d5	d7	b1	b2	b3	C	C0		
PM 08 -00	-502	8	M 12 x 1,5	11,0	30	17	15	10						
measurements [mm]		weight		rotational speed limit		basic load rating								
type	l1	l2	l3	h1	h2	u	z	alpha	alpha prime	Y	gamma	nmax [min-1]	C [N]	C0 [N]
PM 08	46,5	20	72	2,0	2,5	8,5	0,097	1,9	1,81	1225	2605	985		

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952507514
Diâmetro interior	8 mm
Diâmetro exterior	30 mm
Espessura	15 mm
Tipo	SA
Peso	97 g
Linha	Rosca esquerda
Lubrificação	com
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE