

Rótula SA

PM08-02-502-DURBAL - PM08-02-502-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/sa/pm08-02-502-durbal>

PM08-02-502



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]			weight			rotational speed limit			basic load rating		
type	type	d ₁	d ₂	d ₃	d ₄	d ₅	d ₇	b ₁	b ₂	b ₃	C	C ₀	
PM 08 -02	-502	8	M 12 x 1.5	11,0	30	17	15	10					
measurements [mm]		weight		rotational speed limit		basic load rating							
type	l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α [°]	Y	γ ₀	n _{max} [min ⁻¹]	C [N]	C ₀ [N]
PM 08 23	20	48,5	2,0	2,5	8,5	0,088	1,9	1,81	1225	2605	985		

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952507521
Diâmetro interior	8 mm
Diâmetro exterior	30 mm
Espessura	15 mm
Tipo	SA
Peso	88 g
Linha	Rosca esquerda
Lubrificação	com
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE