

Rótula SA

PM15-00-501-DURBAL - PM15-00-501-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/sa/pm15-00-501-durbal>

PM15-00-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]			weight			rotational speed limit			basic load rating			
type	type	d1	d2	d3	d4	d5	d7	b1	b2	b3	Y	C	C0	
PM 15 -00	-501	15	M 20 x 1,5	18,5	42	26	20	14						
measurements [mm]		weight		rotational speed limit		basic load rating								
type	l1	l2	l3	h1	h2	u	z	alpha	alpha prime	Y	C	C0	beta	
PM 15	62,5	30	100	3,0	2,5	6,5				2,07	2,17	975	5485	3270

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952507620
Diâmetro interior	15 mm
Diâmetro exterior	42 mm
Espessura	20 mm
Tipo	SA
Peso	310 g
Linha	Rosca direita
Lubrificação	com
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE