

Rótula SA

PM17-00-502-DURBAL - PM17-00-502-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/sa/pm17-00-502-durbal>

PM17-00-502



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]			measurements [mm]			measurements [mm]						
type	sp/rocthread	sh/rod diam	d ₁	d ₂	d ₄	d ₅	d ₇	b ₁	b ₂	b ₃				
PM 17 -00	-502	17	M 20 x 1,5	21,0	48	25	22	16						
type		measurements [mm]			weight	calculation factors		rotational speed limit	basic load rating					
type	l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α	α'	Y	Y _c	n _{max} [min ⁻¹]	C [N]	C ₀ [N]
PM 17	62,5	36	105	3,5	2,5	7,0	0,401			2,35	2,46	875	5575	2680

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952507675
Diâmetro interior	17 mm
Diâmetro exterior	48 mm
Espessura	22 mm
Tipo	SA
Peso	401 g
Linha	Rosca esquerda
Lubrificação	com
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE