

Rótula SA

PM17-01-502-DURBAL - PM17-01-502-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/sa/pm17-01-502-durbal>

PM17-01-502



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]				measurements [mm]				weight		rotational speed limit		basic load rating		
type	type	d ₁	d ₂	d ₃	d ₄	d ₅	d ₇	b ₁	b ₂	b ₃	weight	calculation factors	rotational speed limit	dyn. C	stat. C ₀	
PM 17 -01	-502	17	M 20 x 1,5	21,0	48	25	22	16								
type		l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α	α'	[kg]	Y	γ ₀	n _{max} [min ⁻¹]	C [N]	C ₀ [N]
PM 17	36	36	78,5	3,5	2,5	7,0					0,354	2,35	2,46	875	5575	2680

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952507682
Diâmetro interior	17 mm
Diâmetro exterior	48 mm
Espessura	22 mm
Tipo	SA
Peso	354 g
Linha	Rosca esquerda
Lubrificação	com
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE