

# Rótula SA

## PM17-01-502-DURBAL - PM17-01-502-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/sa/pm17-01-502-durbal>

### PM17-01-502



**male thread:**  
long-term lubrication, low maintenance, shields

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**

**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

**inner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to ISO/A H1

**lubrication fitting:**  
DIN 3405 D1/A

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

order number		measurements [mm]		measurements [mm]		weight		rotational speed limit		basic load rating			
type	type	d <sub>1</sub>	d <sub>2</sub>	d <sub>4</sub>	d <sub>7</sub>	b <sub>1</sub>	b <sub>2</sub>	Y	Y <sub>0</sub>	C	C <sub>0</sub>		
PM 17 -01	-502	17	M 20 x 1,5	21,0	48	25	22	16					
type		l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	h <sub>1</sub>	h <sub>2</sub>	u	z	α	α'			
PM 17	36	36	78,5	3,5	2,5	7,0	0,354		2,35	2,46	875	5575	2680

## CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952507682
Diâmetro interior	17 mm
Diâmetro exterior	48 mm
Espessura	22 mm
Tipo	SA
Peso	354 g
Linha	Rosca esquerda
Lubrificação	com
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE