

Rótula SI

BRF08-60-502-DURBAL - BRF08-60-502-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/brf08-60-502-durbal>

BRF08-60-502



DURBAL® heavy-duty rod ends with integral self-aligning ball bearing in stainless steel

rod end housing: stainless steel 1.4034, hardened, bearing race superfinished

inner ring: stainless steel, hardened, surface superfinished

lubrication: aluminium-complex soap-grease, temperature range: -45 °C to +120 °C, approval according to USDA H1

lubrication fitting: DIN 3405 D1/A (sizes 6 to 10), DIN 71 412 H1 (sizes 12 to 20)

bearing clearance: 10 - 30 µm radial

tolerances: see page 10

female thread: long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

order number		measurements [mm]										
type	right-hand thread	left-hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	d ₇	b ₁	b ₂	h
BRF 08-60		-502	8	12,5	M 8	10,5	24	16	12	9,0	36	

type	measurements [mm]			SW	α [°]	weight [kg]	calculation-factors Y	rotational speed limit v ₀ [min ⁻¹]	basic load rating C _r [N]	stat. C _r [N]	
	l	l ₁	l ₂								
BRF 08	16	5,0	12	14	8,5	0,044	1,80	1,89	1300	2800	700

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952509228
Diâmetro interior	8 mm
Diâmetro exterior	24 mm
Espessura	12 mm
Tipo	SI
Peso	44 g
Linha	Rosca esquerda
Lubrificação	com
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE